

Caspian FF

Can be installed in an adjacent room, or storage cupboard, with the warm air outlets positioned at the rear of the appliance and ducted into the adjacent room such as a sports hall or even a narrow corridor, permitting an obstruction free wall space



Features

- Caspian fan convectors are both a practical and high quality heating solution for any commercial project
- Incorporating the latest EC motor technology, which can result in running-cost savings as high as 80%, and with variable speed control as standard, the Caspian delivers heat quickly and quietly. AC motor models are available on request
- Caspian FF are compatible with most types of wet central heating systems, functioning equally efficiently with conventional boilers, biomass technology or ground or air source heat pumps
- The airflow can be reversed so that the warm air is discharged from the lower vent

Caspian TT will be available in Spring 2018. Similar design to Caspian FF with top heat discharge.

Applications

- Education
- Healthcare
- Places of worship
- Leisure and sport
- Office
- Hospitality
- Retail
- Showroom
- Industrial

Motor

EC (BMS compliant) or AC

Finish

Casing: zinc-coated steel 1.2mm
Polyester powdercoated: white RAL 9010
Available to special order in any colour and with anti-microbial or anti-bacterial paint

Filter

Class G3, 100% polyester, non-washable

Installation

Suitable for two-pipe central heating systems
Maximum installation height for high or ceiling mounting, - 4m to underside
Pipework access holes on the rear and underside
Key operated front access panels
Bleed valve accessible on removal of front casing
Unit must be earthed

Commissioning


Check water is hot enough to activate the low temperature cut-out thermostat

Controls

Variable heat output controller (mounted within the products)

Mounting options

Rear outlet



Caspian FF



Can be installed in an adjacent room, or storage cupboard, with the warm air outlets positioned at the rear of the appliance and ducted into the adjacent room such as a sports hall or even a narrow corridor, permitting an obstruction free wall space

Heat output

Model	Heat Output at 80°			Heat Output at 75°			Heat Output at 70°			Heat Output at 65°			Heat Output at 60°		
	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)
Caspian 60	5.3	5.6	5.9	4.8	5.0	5.3	4.3	4.5	4.8	3.7	3.9	4.2	3.1	3.4	3.6
Caspian 90	9.3	9.8	10.3	8.7	9.0	9.6	7.9	8.4	8.9	7.1	7.5	8.0	6.2	6.7	7.1
Caspian 120	13.1	13.8	14.5	11.9	12.4	13.2	10.6	11.2	11.9	9.4	9.9	10.6	8.1	8.8	9.4
Caspian 150	16.6	17.4	18.3	15.2	15.8	16.8	13.6	14.3	15.2	12.1	12.8	13.7	10.7	11.6	12.4
Caspian 180	19.0	19.9	21.0	17.6	18.3	19.5	15.7	16.5	17.6	14.2	15.0	16.1	12.9	13.9	14.9

Model	Heat Output at 55°			Heat Output at 50°			Heat Output at 45°			Heat Output at 40°		
	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)	Low (kW)	Medium (kW)	High (kW)
Caspian 60	2.7	2.9	3.1	2.1	2.3	2.5	1.6	1.8	1.9	1.0	1.1	1.2
Caspian 90	5.4	5.8	6.2	4.5	5.0	5.3	3.5	3.9	4.1	2.4	2.6	2.9
Caspian 120	7.0	7.6	8.1	5.9	6.4	6.9	4.6	5.1	5.4	3.2	3.6	3.9
Caspian 150	9.3	10.0	10.7	8.1	8.7	9.4	6.5	7.1	7.5	4.8	5.3	5.9
Caspian 180	11.2	12.1	12.8	10.0	10.9	11.8	8.2	9.0	9.5	6.6	7.3	8.0

Heat output testing based on BS EN442 using mean water temperature, 18°C entering air temperature, 10° temperature drop

Model	Flow & return connections	Fused spur	Total Power Consumption				Sound Levels			Casting colour
			Low (Watts)	Medium (Watts)	High (Watts)	Water Capacity (Litres)	High (dBA)	Medium (dBA)	Low (dBA)	
Caspian 60	22mm	3A	8	24	40	0.92	50	42	33	white
Caspian 90	22mm	3A	15	43	70	1.50	53	42	34	white
Caspian 120	22mm	3A	13	62	110	2.08	58	46	35	white
Caspian 150	22mm	3A	20	144	177	2.58	59	47	36	white
Caspian 180	22mm	3A	26	124	220	3.18	59	48	38	white

Sound levels measured at 3m in front of the floor mounted model

Correction factors

EAT°C	Mean water temperature °C	
	80 to 40	
15	1.10	
21	0.93	

Factor	Temperature drop °C			
	20	15	10	5
Factor	0.89	0.95	1.00	1.04

How to calculate Mass Flow Rate (L/S)


$$\text{Flow rate (L/S)} = \left[\frac{\text{Total heat emitted from product (kW)}}{(\text{Flow temperature} - \text{Return temperature})} \right] \times 4.186 \text{ (Specific heat)}$$

How to calculate Mean Water Temperature (ΔT)

$$\text{Mean water temperature } (\Delta T) = \left[\frac{\text{Flow temperature} + \text{Return temperature}}{2} \right] - \text{Ambient Temperature}$$

Caspian FF

Can be installed in an adjacent room, or storage cupboard, with the warm air outlets positioned at the rear of the appliance and ducted into the adjacent room such as a sports hall or even a narrow corridor, permitting an obstruction free wall space



Ordering guide

Model	Packed Wt (kg)	AC Codes	EC Codes
Caspian FF 60	24	HPCA23002	HPCA22001
Caspian FF 90	39	HPCA23003	HPCA22002
Caspian FF 120	46	HPCA23004	HPCA22003
Caspian FF 150	61	HPCA23005	HPCA22004
Caspian FF 180	76	HPCA23006	HPCA22005
Rear Outlet			
Caspian FF 60	24	HPCA23007	HPCA22006
Caspian FF 90	39	HPCA23008	HPCA22007
Caspian FF 120	46	HPCA23009	HPCA22008
Caspian FF 150	61	HPCA23010	HPCA22009
Caspian FF 180	76	HPCA23011	HPCA22010

Specification

To specify state:

Fan Convecter with EC motor (or AC), in 1.2mm zinc coated steel, 660mm high and 595mm, 895mm, 1195mm, 1495mm or 1795mm wide. With variable heat output controller. As Smith's Caspian FF 60/90/120/150/180.

Accessories	Product Codes
Plinth to suit low level 60 models - 150mm high (White)	HACA33092
Plinth to suit low level 90 models - 150mm high (White)	HACA33093
Plinth to suit low level 120 models - 150mm high (White)	HACA33094
Plinth to suit low level 150 models - 150mm high (White)	HACA33095
Plinth to suit low level 180 models - 150mm high (White)	HACA33096
Plinth to suit low level 60 models - 150mm high (Black)	HACA33082
Plinth to suit low level 90 models - 150mm high (Black)	HACA33083
Plinth to suit low level 120 models - 150mm high (Black)	HACA33084
Plinth to suit low level 150 models - 150mm high (Black)	HACA33085
Plinth to suit low level 180 models - 150mm high (Black)	HACA33086
Adjustable low temperature cut-out (all Caspian models)	HACA33001
Thermostat T1 (low level models with AC or EC Motors)	HACA33002
Thermostat T2 (low level models with AC Motors)	HACA33036
Thermostat (T1) & auto-speed Control (T2) (Low level models with AC motors)	HACA33003
External Control Harness (models with EC motors)	HHCA33004
Caspian EC linking kit (Alt to EXTCH)	HACA33068
Proportional Heat Output Controller (models with EC motors) 15°-25°C (low level only)	HACA33005
Proportional Heat Output Controller (models with EC motors) Remote Sensor 15°-25°C	HACA33037
Proportional Heat Output Controller (models with EC motors) 11°-21°C (low level only)	HACA33075
Proportional Heat Output Controller (models with EC motors) Remote Sensor 11°-21°C	HACA33076
Remote (Wired) Room Thermostat	HAGA95001
Remote (Wired) Room Thermostat Siemens	HACA33077
Remote (Wireless) Room Thermostat Siemens RF	HACA33074
Remote (Wired) Room Thermostat Siemens Tamper Proof	HAGA95004
Remote (Wired) Room Thermostat Siemens Speed and Temperature Control (EC only)	HACA33078
22mm flexible hoses (pair)	HAGA95003

100mm plinth also available, please contact us for further information

As part our commitment to continuous improvement Smith's Environmental Products may change the specifications of its products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All dimensions are in mm unless otherwise stated.