

# Ecovector® Vertical



Ideal for hallways, corridors, alcoves and other places where space is limited. Ecovector can heat up a room more quickly than radiators, thereby reducing the amount of time your boiler or heat pump is running - making it extremely efficient and cost effective



## Features

- Ideal for new and existing building developments
- Compatible with most types of wet central heating systems, functioning equally efficiently with conventional boilers, biomass technology or ground or air source heat pumps
- Supplied as standard in white but casing can be supplied in any colour

## Applications

- Education
- Healthcare
- Places of worship
- Leisure and sport
- Office
- Hospitality
- Retail
- Showroom
- Industrial
- Residential

## Motor

AC only

## Finish

Front casing and side panels: zinc-coated steel  
Polyester powder-coated RAL 9010

## Installation

Mounting bracket supplied  
Unit must be earthed  
Suitable for two-pipe central heating systems  
Minimum height above floor level 150mm, maximum height above floor level 500mm

## Commissioning

Check water is hot enough to activate the selectable low temperature cut-out thermostat

## Controls

Rocker switch - normal/off/boost  
Low temperature cut-out thermostat set to energise fan at approximately 35°C  
Wireless wall mounted thermostat included with this product


## Specification

To specify state:  
Vertical floor mounted hydronic fan convector in white.  
As Smith's Ecovector Vertical.

# Ecovector® Vertical



Ideal for hallways, corridors, alcoves and other places where space is limited. Ecovector can heat up a room more quickly than radiators, thereby reducing the amount of time your boiler or heat pump is running - making it extremely efficient and cost effective



## Heat output

Model	Room size guide* (m <sup>2</sup> )	Heat Output at 80°		Heat Output at 75°		Heat Output at 70°		Heat Output at 65°		Heat Output at 60°	
		Normal (kW)	Boost (kW)	Normal (kW)	Boost (kW)	Normal (kW)	Boost (kW)	Normal (kW)	Boost (kW)	Normal (kW)	Boost (kW)
Ecovector VE 2500	71	2.5	2.6	2.3	2.4	2.0	2.1	1.9	2.0	1.7	1.8

Model	Room size guide* (m <sup>2</sup> )	Heat Output at 55°		Heat Output at 50°		Heat Output at 45°		Heat Output at 40°	
		Low (kW)	Medium (kW)	Low (kW)	Medium (kW)	Low (kW)	Medium (kW)	Low (kW)	Medium (kW)
Ecovector VE 2500	71	1.5	1.5	1.3	1.3	1.1	1.1	0.9	1.0

Model	Flow & return connections	Mains cable	Transformer	Fused spur	Total Power Consumption		Water Capacity (Litres)	Sound Levels		Casting colour	Fan-only
					Normal (Watts)	Boost (Watts)		Normal (dBA)	Boost (dBA)		
Ecovector VE 2500	15mm	1.5m	n/a	3A	28	36	0.75	36	39	white	n/a

\*Room sizes given in cubic metres for general guidance only based on normal heat output (80°C) for domestic applications - always calculate heat losses. Heat outputs tested in accordance with BS4856 using entering water temperature and 340 l/h (75gph) flow rate. Fan-only option operational only when central heating system is switched off. Sound levels measured at 1.5m.

## Ordering guide

Model	Packed Wt (kg)	Product Codes
Ecovector VE 2500	7	HPEV50021

As part our commitment to continuous improvement Smith's Environmental Products may change the specifications of its products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All dimensions are in mm unless otherwise stated.